

Commercial dishwashers

Freshwater system –
Frontloaders

G 7859



Performance specifications

Shortest programme duration*: 18 Min.
Throughput* crockery items/h:: 247 (plus cutlery)
* hot water (65°C) fill and 400V

Control system

Electronic Multitronic Novo vario controls controls
Number of programmes: 3
Single-knob controls with 'Start' button
3-digit 7-segment display
Adjustable wash temperatures, programme durations and water quantities
Holding time adjustable from 1 to 10 mins.
Temperature adjustable between 30°C and 93°C in main wash and final rinse
Drying selectable
9.5 h delay-start feature
Optical interface for programming and after-sales service

Features

Powerful circulation pump
Profi Monobloc water softener
Drain pump
Hot and cold water connection
Single and three-phase supply
Waterproof System
Electro thermal door lock
Integrated steam condenser

Dispensing technology

Powder detergent dispenser
Dispenser for liquid rinsing agents
Connection for dispenser pump for liquid products DOS G 60 Module

Cleaning technology

Fresh water system
Triple spray arm system on 3 levels
Triple filter combination
Gentle start mechanism through circulation pump speed control

Design

Freestanding front loading machine with bottom-hinged door, slanted fascia, with lid
White casing, plastic lid
2-skin construction
Recycling-friendly design with labelled virgin-polymer components
Large wash cabinet with 2 wash levels

Test certificates

CE / VDE / DVGW / WRAS