

**Commercial
dishwashers**

Freshwater system - Frontloaders

Performance specifications

Throughput* plates/h 100

* hot water (65°C) fill

Control system

Electronic Multitronic Novo vario controls controls

Number of programmes: 5

Single-knob controls with 'Start' button

3-digit 7-segment display

Adjustable wash temperatures, programme durations and water quantities

Holding time adjustable from 1 to 10 mins.

Temperature adjustable between 30°C and 93°C in main wash and final rinse

Filter operating hours counter

Drying selectable

9.5 h delay-start feature

Optical interface for programming and after-sales service

Features

Powerful circulation pump

Profi Monobloc water softener

Drain pump

Steam condenser

Hot or cold water connection

Three-phase supply 220V/60Hz or 440V/60Hz

Waterproof System

Electric door lock

Dispensing technology

Powder detergent dispenser

Dispenser for liquid rinsing agents

Connection for dispenser pump for liquid products DOS C 60 Module

Cleaning Technology

Fresh water system

Triple spray arm system on 3 levels

Triple filter combination

Thermal disinfection programmes

Gentle start mechanism through circulation pump speed control

Design

Freestanding front loading machine with bottom-hinged door, slanted fascia, with lid

Stainless steel casing with stainless steel lid

2-skin construction

Recycling-friendly design with labelled virgin-polymer components

Large wash cabinet with 2 wash levels

Test certificates

CE / VDE / DVGW / Interference suppression

G 7860 (Marine)