

Commercial dishwashers

Tank system - Through-feed

G 8072



Performance specifications

Shortest programme duration*: 60 Sec.
Throughput* plates/h 1080
Baskets*: 60 baskets/h
* hot water (65°C) fill

Control system

Electronic controls
Number of programmes: 3
Membrane switches with LED indicator for tank and boiler temperature
Single-knob controls with colour-coded status indicator
Automatic programme start when hood is closed

Features

45 l tank
7.5 l boiler
Powerful circulation pump
Integrated boiler with pressure-boosting pump for final spray rinse
Final rinse temperature selectable between 85 and 65°C
Level-fill indicators for liquid detergent and rinse aid
Hot water fill possible
Three-phase supply
Single-phase version available

Dispensing technology

Dispenser for liquid rinsing agents
Dispenser pump for liquid detergents optional
Connection of DOS modules C 60, C60/1 and G60 possible

Cleaning technology

Tank system
Suds cleaner
Drain pump
Rotating spray system (top and bottom) with separate spray arms for washing and rinsing
Quadruple filtration system
Cabinet with low-profile heater elements

Design

Hooded pass-through machine
Stainless-steel outer panelling
Linear and corner installations possible
Cabinet and hydraulic circuit made from high-grade stainless steel

Test certificates

DVGW, CE, TÜV, WRAS