

Laundry equipment

Washer-extractors

WS 5073 (Mop)



Performance specifications

Load ratio: 7,5 kg
Drum volume: 73 l
Spin speed: 1200 rpm
g-factor: 450

Control system

Electronic controls
7 fixed programmes (including 4 special mophead programmes: 'Thermal disinfection', 'Chemo-thermal disinfection', 'Pads' and 'Short').
Additional user-programmable functions (PFT)
Programme sequence display
Temperature and countdown indicators
Pushbutton for door release

Drive

Digitally controlled d.c. motor
Variable wash and spin speeds

Features

Dump valve flanged directly onto suds container
Hot and cold water connection
Coin mechanism connection option
Connection of 3 dispenser pumps possible

Heating

Electric

Dispensing technology

Single compartment dispenser in machine lid.

Wash technology

Scoop-and-ladle technology
Gentle start mechanism
Graduated spin
Interim spin

Design

Freestanding washer-extractor
Machine front and lid in stainless steel, galvanised, blue powder-coated side panels
Stainless-steel suds container and drum
Extruded drum perforations
Large door with wide opening angle, door without concertina seal
Recycling-friendly design with labelled virgin polymers
Dimensions:
H x W x D: 102 x 73 x 71 cm

Test certificates

DVGW (Water)
Splash-proof
EMV-CE